FUJITSU

Data Sheet FUJITSU Desktop ESPRIMO P420 E85+

Your Immediately Deliverable Office PC

The FUJITSU ESPRIMO P420 delivers high-quality computing for your office applications and projects at a very attractive price point. You can choose cost-optimized fixed configurations for immediate delivery. Alternatively, you can use configuration options to meet your specific hardware needs, while staying within your budget.

High performance and best price/performance ratio

- Cost-effective system for price-conscious customers
- 4th generation Intel[®] Core[™] processor family

Flexibility

- Freedom of choice with tailored systems, perfect fit for specific requirements
- Flexible logistic concept optional customizing program

Reliability

- High-quality and functional stability
- Development and production in Europe

Lifecycle

- Hardware continuity for long-term projects
- Managed lifecycle up to 12 months

Meets ENERGY STAR® requirements

Low power consumption and low costs, without any loss in performance Power supply with 85% efficiency





Components

Processor	Intel® Core™ i7-4790 processor (4 Cores / 8 Threads, 3.60 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 4600) *
	Intel® Core™ i5-4690 processor (4 Cores / 4 Threads, 3.50 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 4600) *
	Intel® Core™ i5-4590 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.7 GHz, 6 MB, Intel® HD Graphics 4600) *
	Intel [®] Core™ i5-4460 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.4 GHz, 6 MB, Intel [®] HD Graphics 4600)
	Intel® Core™ i3-4170 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 4400)
	Intel [®] Pentium [®] processor G3460 (2 Cores / 2 Threads, 3.50 GHz, 3 MB, Intel [®] HD Graphics)
	Intel [®] Pentium [®] processor G3260 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel [®] HD Graphics)
	Intel [®] Celeron [®] processor G1840 (2 Cores / 2 Threads, 2.80 GHz, 2 MB, Intel [®] HD Graphics)
	*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other
	variables)
perating systems	
Operating system	Windows 10 Pro
	Windows 8.1 Pro
	Windows 8.1 Windows 7 Professional 64-bit
	Windows 7 Professional 64-bit Windows 7 Professional 32-bit
Operating system compatible	Windows 10 Pro (license + recovery media only)
system compatible	openSUSE Linux
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM
	8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM
Hard disk drives (internal)	SSD SATA III Premium, 512 GB, 2.5-inch
	SSD SATA III Premium, 256 GB, 2.5-inch
	SSD SATA III Premium, 128 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch, SED
	SSD SATA III, 128 GB, 2.5-inch, SED
	SSHD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	SSHD SATA III, 5,400 rpm, 500 GB, 2.5-inch
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch
	HDD SATA II, 5,400 rpm, 320 GB, 2.5-inch
Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery
	SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk)
	SED (Self-Encrypting Drive)
iraphics	NVIDIA® NVS™ 315, 1 GB
e.epines	NVIDIA® GeForce® GTX 745 2 GB FH, 2 GB
	NVIDIA® GeForce® GT630 DisplayPort 2GB FH, 2 GB
	NVIDIA® GeForce® 605 DisplayPort 1GB FH, 1 GB
	LFH59/ 2x DVI-I adapter cable
	LFH59/ 2x DP adapter cable
	DVI-I to VGA Adapter
	DP to DVI-D (single link) Adapter Cable
	ATI Radeon® HD7350 1GB FH, 1 GB

Drives (optional)	BD Triple Writer SATA slim (tray)
	DVD-ROM
	DVD Super Multi
	MultiCard Reader 24in1 USB 2.0 3.5"
Interface add on cards/components (optional)	
	USB 3.0 PCIe x1
	Gigabit Ethernet PCIe x1, DS
	Dual serial card PCIe x1

Base unit

Base unit	ESPRIMO P420 E85+		
Mainboard			
Mainboard type	D3230		
Formfactor	μΑΤΧ		
Chipset	Intel® H81		
Processor socket	LGA 1150		
Processor quantity maximum	1		
Supported capacity RAM (max.)	16 GB		
Memory slots	2 DIMM (DDR3)		
Memory frequency	1,600 MHz		
Memory notes	Dual channel support For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).		
LAN	10/100/1,000 MBit/s Realtek RTL8111G		
BIOS version	AMI Aptio 4.6		
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)		
Audio type	On board		
Audio codec	Realtek ALC671		
Audio features	High Definition Audio, 5.1 surround sound		
I/O controller on board			
Serial ATA total	3		
thereof SATA III	2		
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI		
Interfaces			
Audio: line-in	1		
Audio: line-out	1		
Front audio: microphone	1		
Front audio: headphone	1		
USB 2.0 total	6		
USB 3.0 total	2		
USB front	2x 2.0		
USB rear	2x 2.0/ 2x 3.0		
USB internal	2x 2.0		
VGA	1		
DVI	1 (DVI-D)		

Interfaces	
Mouse / Keyboard (PS/2)	1/1
Ethernet (RJ-45)	1
· · ·	
Input device / components	
	Optical USB wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO
	Mouse M440 ECO
Drive bays	
Drive bays total	5
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2
Drive bay notes	3,5" bay can be used for 2,5" drives
Slots	1 v /210 mm / 0.27 in th) Full height
PCI-Express 2.0 x16	1 x (210 mm / 8.27 inch) Full height
PCI-Express x1	2 x (190 mm / 7.48 inch) Full height
Graphics on board	
Graphics brand name	Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor)
Shared video memory	up to 1,782 MB
TFT resolution (VGA)	1,024 x 768 pixel
	1,280 x 1,024 pixel 1,360 x 768 pixel
	1,440 x 900 pixel
	1,600 x 900 pixel
	1,600 x 1,200 pixel
	1,680 x 1,050 pixel 1,920 x 1,080 pixel
TFT resolution (DVI)	1,280 x 1,024 pixel
	1,360 x 768 pixel
	1,440 x 900 pixel
	1,600 x 900 pixel
	1,680 x 1,050 pixel
	1,920 x 1,080 pixel 1,920 x 1,200 pixel
Graphics features	Dual display support
	DirectX [®] 11.1
	HDCP support
	Open CL® 1.2
Craphics pates	OpenGL® 4.0
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 83% / 86% / 85%
	0-Watt mode with hard-off switch
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	No

Power consumption			
Power consumption note	See white paper Energy Consumption 0-Watt mode with hard-off switch		
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=f4725e85-5d74-41f1-99a0-7ef55a8d713d		
Heat dissipation			
Heat dissipation notes	See white paper Energy Consumption		
Noise emission			
Related Processors for noise	Intel® Core™ i7 4770		
Standard noise emission	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74		
Standard noise notes / description	Bystander position		
Standard noise operation mode: CPU 50% load	3.4 B / 21 dB(A) Bystander; 25 dB(A) Operator position		
Standard noise operation mode: HDD load	3.4 B / 21 dB(A) Bystander; 26 dB(A) Operator position		
Standard noise operation mode: Idle mode	3.4 B / 20 dB(A) Bystander; 26 dB(A) Operator position		
Standard noise operation mode: ODD load	4.6 B / 32 dB(A) Bystander; 38 dB(A) Operator position		
Standard noise operation mode: Office applications 2.0	3.4 B / 20 dB(A) Bystander; 26 dB(A) Operator position		
Dimensions / Weight / Environmental			
Dimensions (W x D x H)	175 x 425 x 353 mm		
	6.89 x 16.74 x 13.9 inch		
Operating position	Vertical		
Weight	9 kg		
Weight (lbs)	20.22 lbs		
Weight notes	Actual weight may vary depending on configuration		
Operating ambient temperature	10 - 35 ℃ (50 - 95 °F)		
Operating relative humidity	5 - 85 % (relative humidity)		
Compliance			
Product	ESPRIMO P420		
Model	MI4W		
Germany	TÜV GS		
Europe	CE		
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) EPEAT® Gold (dedicated regions) ENERGY STAR® 6.0 (dedicated regions)		
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates		
Additional Software			
Additional software (preinstalled)	Workplace Protect (secure authentication solution) Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office)		
Additional software (optional)	Recovery DVD for Windows [®] Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL		

Manageability		
Manageability technology	DeskUpdate Driver management	
manageability technology	PXE 2.1 Boot code	
	Wake up from S5 (off mode)	
	WoL (Wake on LAN)	
Supported standards	DMI (Desktop Management Interface)	
	SMBIOS (System Management BIOS) PXE (Preboot Execution Environment)	
	WMI (Windows Management Instrumentation)	
	WBEM (Web Based Enterprise Management)	
	CIM (Common Information Model)	
Security		
Physical Security	Kensington Lock support	
	Eye for padlock	
System and BIOS Security	Boot sector virus protection Write protect option for the Elech EDDOM	
	Write protect option for the Flash EPROM Control of external interfaces	
User Security	User and supervisor BIOS password	
,	Hard disk password	
	Access protection via external SmartCard reader (optional)	
	Access protection via internal SmartCard reader (optional)	
Miscellaneous		
Packaging information		
Packaging dimension (mm)	516 x 278 x 562 mm	
Packaging dimension (inch)	20.31 x 10.94 x 22.13 inch	
Max. quantity / pallet	24	
Material - Weight (g) Carton	1280 g	
Material - Weight (lbs) Carton	2.82 lbs	
Material - Weight (g) EPS / PS	140 g	
Material - Weight (lbs) EPS / PS	0.31 lbs	
Material - Weight (g) PE	60 g	
Material - Weight (lbs) PE	0.13 lbs	
Packaging notes	printed user documentation is bleached in chlorine free process	
Warranty		
Warranty period	1 year	
Warranty type	, Bring-In / Onsite Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 1 year material warranty)	
Warranty Terms & Conditions Product Support Services - the perfec	http://support.ts.fujitsu.com/warranty t <mark>extension</mark>	
Recommended Service	9x5, Onsite Response Time: Next Business Day	
Spare Parts availability	5 years after end of product life	
Service Weblink	http://www.fujitsu.com/fts/services/support	

Recommended Accessories

Display E19-7 LED

The FUJITSU Display E19-7 LED combines comfortable ergonomics with best-in-class energy saving technology like ECO operation mode.

Order Code: S26361-K1482-V160

Display B24W-7 LED	The FUJITSU B24W-7 LED Display with excellent ergonomics makes intensive office work extremely comfortable. This highly reliable display offers superb usability and power-saving features to help reduce your labor as well as energy costs. With wide viewing angle technology, flexible connectivity, and easy manageability, the FUJITSU B24W-7 LED Display can help you improve productivity.	
Mouse M440 ECO	Fujitsu Mouse M440 ECO is made from 100% bio material and has a completely PVC free cable. The elegant M440 ECO works on nearly every surface and follows all your hand movements smoothly and precisely. It features two main buttons and as well as a scroll wheel providing comfortable computing to both right and left-handed users.	Order Code: S26381-K450-L200
SOUNDSYSTEM DS E2000 Air	The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.	Order Code: S26391-F7128-L600
UC&C USB Headset Stereo H650e	The UC&C USB Headset Stereo H650e is the ultimate in style and functionality. Long, uncomfortable work calls are a thing of the past thanks to the cushioned ear pads and crystal clear sound. Adjustable headband and microphone provides the perfect fit for everyone. Optimized for Microsoft [®] Lync [™] the headset displays a red 'in-call' LED to let your co-workers know when you're available, thus helping to boost office productivity.	Order Code: S26391-F7139-L10
HS E2000 Communicator Headset	The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.	Order Code: S26391-F7139-L5
Keyboard KBPC PX ECO	Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.	S26381-K341-L1** (**: country specific variation)
Keyboard KB900	The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidently spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.	S26381-K560-L4** (**: Country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Desktop ESPRIMO P420 E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO P420 E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/ terms

© 2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions GmbH Website: www.fujitsu.com/fts 2016-02-01 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms

© 2016 Fujitsu Technology Solutions GmbH